


OR-BOLT

STAINLESS STEEL

JN

Technical Data

NEW



| SIZE | RIVET CODE | RIVET LENGTH L ± 0.3 | GRIP RANGE G | $\varnothing A$ ± 0.07 | $\varnothing D$ $+ 0.09 / - 0.05$ | E ± 0.3 | X max | $\varnothing H$ ± 0.3 | M ± 2 | BLIND SIDE PROTRUSION N max |
|--------|------------|-----------------------------|-----------------|-------------------------------|--------------------------------------|----------------|-------|------------------------------|--------------|--------------------------------|
| 6.5 mm | JN65166 K | 16.6 | 3.2 - 12.1 | 4.00 | 6.50 | 2.0 | 1.0 | 9.8 | 57 | 26.3 |

| RIVET CODE | SHEAR STRENGTH, N / Kgf | | TENSILE STRENGTH, N / kgf | |
|------------|-------------------------|--------------|---------------------------|--------------|
| | min. | typical. | min. | typical. |
| JN 65166 K | 10675 / 1088 | 11700 / 1190 | 8229 / 838 | 10400 / 1060 |

| | |
|-----------------------|-----------------------------|
| BODY MATERIAL | STAINLESS STEEL AISI 304 Cu |
| MANDREL MATERIAL | STAINLESS STEEL AISI 304 Cu |
| RECOMMENDED HOLE SIZE | 6.60 - 6.90 mm |



Fastening Solutions

ORNIT BLIND RIVETS

Tel: +972 8 6610222, Fax: +972 8 6611380

www.ornit.com