

STELOCK



STEEL/STEEL


Dia 4.0mm, 4.8mm, 6.0mm

Technical Data

STELOCK

NEW TYPE

DOME HEAD



NOM. SIZE	ORNIT CODE	IDENTIFICATION	L LENGTH +/-0,3	G GRIP min-max	M +/- 2,0	N max	A +/-0,05	D +/-0,1	E +/-0,25	H +/-0,3
	* SL40077D	SL-DOME-0509	7.7	1.0-3.0	44	10.2				
5/32"	SL40097D	SL-DOME-0512	9.7	3.0-5.0	46	12.2	2.57	4.0	1.30	7.7
4.0mm	*SL40127D	SL-DOME-0516	12.7	5.0-7.0	49	15.2				

NOM. SIZE	ORNIT CODE	IDENTIFICATION	L LENGTH +/-0,3	G GRIP min-max	M +/- 2,0	N max	A +/-0,05	D +/-0,10	E +/-0,25	H +/-0,3
	SL48088D	SL-DOME-0611	8.8	1.5-3.5	47	12.0				
3/16"	SL48113D	SL-DOME-0614	11.3	3.5-6.0	50	14.5	3.05	4.85	1.30	9.3
4.8mm	SL48143D	SL-DOME-0618	14.3	6.0-8.5	53	17.5				

NOM. SIZE	ORNIT CODE	L LENGTH +/-0,3	G GRIP min-max	M +/-2,0	N max	A +/-0,05	D +0,08/-0,10	E +/-0,25	H +/-0,3
	SL60100 D	10,0	1,5-4,0	49	14,2	3,98	6,00	1,80	12,0
	SL60130 D	13,0	3,0-6,0	52	17,2	3,98	6,00	1,80	12,0
	SL60160 D	16,0	6,0-9,0	55	20,2	3,98	6,00	1,80	12,0
	SL60190 D	19,0	9,0-12,0	58	23,2	3,98	6,00	1,80	12,0

ORNIT BLIND RIVETS



Tel: +972 8 6610222, Fax: +972 8 6611380

www.ornit.com