

Orlock Steel

Protruding Head

Before Installation


After Installation

Body Material: Low Carbon Steel

Body Finish: Zinc Plated Cr VI free

Mandrel Material: Carbon Steel

Mandrel Finish: Zinc Coated Cr VI free



Dimensions - Nominal (millimeter)

Forces - Nominal (Kgf)

ART.No	MIN	MAX									
4.8	4.9-5.1	L48090P	9.0	1.5	3.5	2.2	9.8	3.0	460	360	5,000
		L48115P	11.5	3.5	6.0				610		4,000
		L48140P	14.0	6.0	8.5				640		3,000
		L48165P	16.5	8.5	11.0						2,500
		L48190P	19.0	11.0	13.5						2,000
6.4	6.6-6.8	L64090P	9.0	1.5	3.5	3.0	13.0	4.2	700	660	2,000
		L64105P	10.5	2.8	4.8				940		2,000
		L64111P	11.1	3.4	5.4						2,000
		L64125P	12.5	4.8	6.8				1040		2,000
		L64145P	14.5	6.8	8.8				1140		2,000
		L64165P	16.5	8.8	10.8						2,000
		L64185P	18.5	10.8	12.8						2,000
		L64205P	20.5	12.8	14.8						2,000
		L64225P	22.5	14.8	16.8						1,000
		L64245P	24.5	16.8	18.8						1,000
		L64265P	26.5	18.8	20.8						1,000
		L64285P	28.5	20.8	22.8						1,000
		* L64305P	30.5	22.8	24.8						1,000
		* L64325P	32.5	24.8	26.8						1,000
		* L64355P	35.5	25.8	28.8						1,000
* L64375P	37.5	27.8	30.8		1,000						
* L64395P	39.5	29.8	32.8		1,000						
7.8	8.0-8.3	L78135P	13.5	4.0	7.0	3.7	16.0	5.1	1410	930	1,000
		L78165P	16.5	7.0	10.0				1600		1,000
		L78195P	19.5	10.0	13.0						1,000
		L78225P	22.5	13.0	16.0						1,000
		* L78255P	25.5	16.0	19.0						1,000
		* L78285P	28.5	19.0	22.0						500
		* L78315P	31.5	22.0	25.0						500

* UNDER SPECIAL REQUEST

ORNIT Blind Rivets, Kibbutz Or-Haner, M.P. Hof Ashkelon 79190, ISRAEL

Tel: +972-8661-0222, Fax: +972-8661-1380, E-Mail: info@ornit.com



www.ornit.com