

Orlock Aluminium

Protruding Head

Before Installation


After Installation

Body Material: Aluminium Alloy - AlMg 2.5 (5052)

Body Finish: Bright Finish Surface

Mandrel Material: Aluminium Alloy - AlMg 5.0 /6.0 or equivalent

Mandrel Finish: Natural



Dimensions - Nominal (millimeter)

Forces - Nominal (Kgf)

Diameter	Thread	ART.No	Length	Head		Body	Thread	Thread	Thread	Forces		Box
				MIN	MAX					MIN	MAX	
4.8	4.9-5.1	LH48090P	9.0	1.5	3.5	2.2	9.8	3.0	260	170	180	1,000
		LH48115P	11.5	3.5	6.0						1,000	
		LH48140P	14.0	6.0	8.5						1,000	
		LH48165P	16.5	8.5	11.0						1,000	
		LH48190P	19.0	11.0	13.5						1,000	
		LH48225P	22.5	13.0	15.0						1,000	
6.4	6.6-6.8	LH64105P	10.5	2.8	4.8	3.0	13.0	4.2	500	350	430	2,000
		LH64125P	12.5	4.8	6.8						2,000	
		LH64145P	14.5	6.8	8.8						2,000	
		LH64165P	16.5	8.8	10.8						2,000	
		LH64185P	18.5	10.8	12.8						2,000	
		LH64205P	20.5	12.8	14.8						2,000	

ORNIT Blind Rivets, Kibbutz Or-Haner, M.P. Hof Ashkelon 79190, ISRAEL

Tel: +972-8661-0222, Fax: +972-8661-1380, E-Mail: info@ornit.com

www.ornit.com

