

# Super Orlock Steel

## Protruding Head

### HIGH STRENGTH LARGE GRIP RANGE

**Body Material:** Carbon Steel

**Body Finish:** Zinc Plated Cr VI free


**Mandrel Material:** Carbon Steel

**Mandrel Finish:** Zinc Plated Cr VI free

Before Installation













After Installation



Dimensions - Nominal (millimeter)

Forces - Nominal (Kgf)

6.5	6.7-6.9	ART.No												
						MIN	MAX							
		LS65105P	10.5		2.0	4.5						1,100		2,000
		LS65125P	12.5		3.0	6.5						1,250		2,000
		LS65145P	14.5		5.0	8.5	3.0	13.0	4.2			1,400	810	2,000
		LS65165P	16.5		7.0	10.5						1,450		2,000
		LS65185P	18.5		9.0	12.5						1,570		2,000
		LS65205P	20.5		11.0	14.5								2,000
		LS65225P	22.5		13.0	16.5								1,000



ORNIT Blind Rivets, Kibbutz Or-Haner, M.P. Hof Ashkelon 79190, ISRAEL

Tel: +972-8661-0222, Fax: +972-8661-1380, E-Mail: info@ornit.com

[www.ornit.com](http://www.ornit.com)

