

# Orlock Steel Plywood

## Protruding Head

Before Installation


After Installation

**Body Material:** Low Carbon Steel, SAE 1006-1022

**Body Finish:** Zinc Plated Cr VI free

**Mandrel Material:** Carbon Steel, SAE 1015-1040

**Mandrel Finish:** Zinc Coated Cr VI free



**Dimensions - Nominal (millimeter)**

**Forces - Nominal (Kgf)**

6.4	6.6-6.8 *	ART.No	MIN	MAX	3.0	13.0	4.17	1140	600	1,000
		LP64245P	24.5	14.8	16.8					1,000
		LP64265P	26.5	16.8	18.8					1,000
		LP64285P	28.5	18.8	20.8					1,000
		LP64315P	31.5	20.8	22.8					1,000
	*	LP64335P	33.5	22.8	24.8					1,000
	*	LP64365P	36.5	24.8	26.8					1,000
	*	LP64385P	38.5	26.8	28.8					1,000
	*	LP64405P	40.5	28.8	30.8					1,000

\* UNDER SPECIAL REQUEST



**ORNIT Blind Rivets**, Kibbutz Or-Haner, M.P. Hof Ashkelon 79190, ISRAEL

Tel: +972-8661-0222, Fax: +972-8661-1380, E-Mail: info@ornit.com

[www.ornit.com](http://www.ornit.com)

